

# PNEU-SHOP.FR

R888R gomme GG	charge	vitesse	Diamètre en mm	Bande de roulement en mm	Jantes conseillées	
					Idéales	Utilisables
<b>13</b>						
185.60 R 13	80	V	552	189	5.5	5-6.5
205.60 R 13	86	V	576	209	6	5.5-7.5
225.45 R 13	84	V	532	225	7.5	7-8.5
<b>14</b>						
185.60 R 14	82	V	578	189	5.5	5-6.5
<b>15</b>						
195.55 R 15	89 XL	V	595	201	6	5.5-7
195.50 R 15	82	V	577	201	6	5.5-7
205.50 R 15	89 W	W	587	214	6.5	5.5-7.5
225.50 R 15	91	W	607	233	7	6-8
235.50 R 15	94	W	617	245	7.5	6.5-8.5
225.45 R 15	91 XL	W	583	225	7.5	7-8.5
<b>16</b>						
205.55 R 16	94	W	632	214	6.5	5.5-7.5
195.50 R 16	84	W	602	214	6	5.5-7
205.50 R 16	87	W	612	214	6,5	5.5-7.5
205.45 R 16	87 XL	W	590	206	7	6,5-7,5
225.45 R 16	93 XL	W	608	225	7.5	7-8.5
245.45 R 16	94	W	626	243	8	7.5-9
255.50 R 16	99	W	662	265	8	7-9
<b>17</b>						
205.50 R 17	89	W	638	214	6,5	5,5-7,5
205.45 R 17	88	W	616	206	7	6,5-7,5
205.40 R 17	84 W		599	212	7.5	7-8
215.45 R 17	91	W	626	213	7	7-8
225.45 R 17	94	W	634	225	7.5	7-8.5
235.45 R 17	94	W	644	236	8	7.5-9
235.40 R 17	94	W	620	241	8.5	8-9.5
245.40 R 17	95	XL	628	248	8.5	8-9.5
255.40 R 17	98	W	636	260	9	8.5-10
275.40 R 17	98	W	652	278	9.5	9-11
<b>18</b>						
225.40 R 18	92 XL	Y	637	230	8	7.5-9
235.40 R 18	95	Y	645	241	8.5	8-9.5
245.40 R 18	97 XL	Y	653	248	8.5	8-9.5
255.35 R 18	94 XL	Y	635	260	9	8.5-10
265.35 R 18	97	Y	643	271	9.5	9-10.5
275.35 R 18	99	Y	649	278	9.5	9-11
295.30 R 18	98	Y	635	301	10.5	10-11
<b>19</b>						
235.35 R 19	91	Y	652	240	8.5	8-9.5
275.35 R 19	96	Y	675	278	9,5	9-11
285.35 R 19	99	Y	683	290	10	9,5-11
265.30 R 19	93 XL	Y	643	271	9	9-11
295.30 R 19	100	Y	661	301	10.5	10-11
305.30 R 19	102	Y	667	313	11	10.5-11.5
<b>20</b>						
255.35 R 20	93	Y	686	260	9	8,5-10
285.35 R 20	100	Y	710	290	10	9,5-11
285.30 R 20	95	Y	680	290	10	9,5-10,5
315.30 R 20	101	Y	703	320	11	10,5-11,5

